



# HERAPAINT LAVABILE

Matt washable wall paint for interiors

## TECHNICAL FEATURES

**HERAPAINT LAVABILE** is a washable wall paint for interiors, formulated according to the high quality standards of the **HERAKEM** laboratory with modified synthetic resins in aqueous emulsion and selected mineral fillers, guaranteeing permeability to water vapor, high coverage, opacity and whiteness.

**HERAPAINT LAVABILE** is characterized by excellent brushability and dilatation. It adheres perfectly to all types of masonry, plasters, smoothing compounds and old, non-chalking and well-adhering paints. Equipped with a high leveling power, **HERAPAINT LAVABILE** creates surfaces with low dirt retention, with a pleasant aesthetic appearance, successfully used for prestigious interiors where a soft and velvety finish to the touch with a masking opaque effect is required.

## FIELD OF APPLICATION

**HERAPAINT LAVABILE** can be applied indoors, on cementitious substrates, lime, gypsum, both new and well seasoned and old, as long as they are cohesive, well adherent and not chalking. It can also be applied outdoors on covered surfaces protected from direct exposure to light and rain; such as, for example, broken out of balconies, hallways, stairways, under balconies, internal parapets of terraces.

## APPLICATION CYCLE

### Preparation of the substrate

Make sure that the substrate is dry, cured and not chalking. If necessary, refurbish or consolidate with specific products. In the presence of mold, treat the surface with the appropriate detergents. Remove by brushing, or by washing, all traces of dirt, and the flaking parts of old paint, (in the case of lime or tempera paints, all the old whitening must be removed) and any efflorescence. Remove dust, smog and other deposits by brushing.

Holes, cracks, cracks and depressions can be treated with the **HERAKEM** smoothing line according to the thickness to be created and the type of substrate to be treated. Make sure that the substrate and the repairs carried out are dry and apply a layer of **HERALAX FOND** wall fixative sealer.

## FINISH

Allow the substrate to dry perfectly, apply two coats of **HERAPAINT LAVABILE** with an interval of about 8 – 10 hours between each other.

**HERAPAINT LAVABILE** can be applied by brush, roller or spray and must be diluted with clean water in the proportions indicated in the table. During the dilution phase, be careful to homogenize the product well, using a low speed mixer if possible.

## CLEANING

The tools used for laying can be cleaned with water before the product hardens.

## ITEM OF SPECIFICATIONS

The protection and decoration of internal walls, of plasters or smoothing, based on cement, lime or gypsum, both new well seasoned and old, as long as they are cohesive, well adherent and not crumbling and on the outside of old or new cementitious surfaces, even already painted, provided that in non-critical environmental conditions on surfaces covered and protected from direct exposure to sunlight and rain, it must be carried out by applying a smooth, opaque and opaque washable paint, based on modified acrylic resins in aqueous dispersion such as **HERAPAINT LAVABILE** from **HERAKEM SRL**.



## WARNINGS

- Apply with a relative humidity of the environment: <85%
- Apply at temperatures included: Min. +5 ° C / Max. +35 ° C
- Do not apply on external surfaces exposed to rain or direct sunlight.
- Application on surfaces with saline efflorescence or subject to rising humidity does not guarantee the adhesion of the product to the substrate.

## TECHNICAL DATA \*(at +22±1°C and 55±5% R.H.)

Appearance and finish	very matt	Dry in depth	max 10 - 12 hours
Specific weight (g / liter)	approx. 1500 – 1550	Thinner	water
Brookfield viscosity	approx. 15.000 – 18.000 CPS	Dilution	up to 25%
Color range	white	Over-paintable	8 – 10 hours
Flash point	non-flammable	Customs heading	3209 1000 00
Tools	brush - roller - spray	Storage	12 months in original and dry packaging
Touch dry	1 - 2 hours		

<b>Consumption</b>	<b>9 - 11 m<sup>2</sup>/L per coat</b>	<b>Packaging</b>	<b>14 Lt and 5 Lt drums</b>
--------------------	--	------------------	-----------------------------

### PRODUCT FOR PROFESSIONAL USE ONLY

All the data and indications given in this technical data sheet, although resulting from laboratory tests carried out and from our direct application experiences, due to the infinite number of variables linked to the construction site conditions, are to be considered, in any case, purely indicative. Therefore, before applying the product, the user is required to establish whether it is suitable for the use envisaged by him, in the specific hygrothermal and application conditions foreseen at the time of use and, in any case, he assumes all responsibility for it. We are not liable for damage to people or things deriving from improper use of the product. We reserve the right to modify the data contained therein as a result of improvements and technical progress.