# ECOLINE LAVABILE

**Washable wall paint for interiors with a matt effect**

## TECHNICAL FEATURES

**ECOLINE LAVABILE** is a washable wall paint for interior opaque, with high hiding power, excellent whiteness, good breathability and brushability, consisting of synthetic resins in aqueous emulsion, titanium dioxide, very white micronized fillers, specific additives, formulated according to high standards qualitatives of the **HERAKEM** laboratory. Excellent for interior painting where a product with good resistance to washing and low dirt pick-up is required, with a soft and velvety finish to the touch, white, opaque and with excellent expansion.

## FIELD OF APPLICATION

**ECOLINE LAVABILE** can be applied indoors, on cementitious substrates, lime, gypsum, both new and well seasoned and old, as long as they are cohesive, well adherent and not crumbling, in particular for the painting of prestigious environments where a smooth appearance is required. matte and soft to the touch.

## APPLICATION CYCLE

### Preparation of the substrate

Make sure that the substrate is dry, cured and not chalking. If necessary, refurbish or consolidate with specific products. In the presence of mold, treat the surface with suitable detergents. Remove by brushing, or by washing, all traces of dirt, and the flaking parts of old paint, (in the case of lime or tempera paints, all the old whitening must be removed) and any efflorescence. Remove dust, smog and other deposits by brushing.

Holes, cracks, cracks and depressions can be treated with the **HERAKEM** smoothing line according to the thickness to be created and the type of substrate to be treated. Make sure that the substrate and the repairs carried out are dry and apply a layer of **HERALAX FOND** wall fixative sealer.

## FINISH

Allow the substrate to dry perfectly, apply two coats of ECOLINE LAVABILE with an interval of about 8 – 10 hours between each other. **ECOLINE LAVABILE** can be applied by brush, roller or spray and must be diluted with clean water in the proportions indicated in the table. During the dilution phase, be careful to homogenize the product well, using a low speed mixer if possible.

## CLEANING

After use, the tools must be cleaned with water and if the product is dry, it is recommended to remove it with white spirit or hot water.

## ITEM OF SPECIFICATIONS

The decoration of internal surfaces will be carried out by applying white tempera paint, consisting of vinyl resins in aqueous emulsion, micronized fillers and specific additives such as **ECOLINE LAVABILE** by **HERAKEM SRL**.

## WARNINGS

- Apply with a relative humidity of the environment: <85%
- Apply at temperatures included: Min. +5 ° C / Max. +35 ° C
- Do not apply on external surfaces
- Application on surfaces with saline efflorescence or subject to rising humidity does not guarantee the adhesion of the product to the substrate.

## TECHNICAL DATA *(at +22±1°C and 55±5% R.H.)

| | | | |
|---|---|---|---|
| Appearance and finish | very matt | Touch dry | 1 - 2 hours approx. |
| Specific weight (g / liter) | approx. 1530 – 1580 | Dry in depth | max 10 - 12 hours |
| Brookfield viscosity | approx. 12.000 – 16.000 CPS | Thinner | water |
| Color range | white | Dilution | 20 - 30% according to the type of application |
| Flash point | non-flammable | Over-paintable | 8 – 10 hours |
| Tools | brush - roller - spray | Customs heading | 3209 1000 00 |

| | | | |
|---|---|---|---|
| **Consumption** | **10 - 12 m²/L per coat** | **Packaging** | **14 Lt and 5 Lt drums** |

**PRODUCT FOR PROFESSIONAL USE ONLY**

All the data and indications given in this technical data sheet, although resulting from laboratory tests carried out and from our direct application experiences, due to the infinite number of variables linked to the construction site conditions, are to be considered, in any case, purely indicative. Therefore, before applying the product, the user is required to establish whether it is suitable for the use envisaged by him, in the specific hygrothermal and application conditions foreseen at the time of use and, in any case, he assumes all responsibility for it. We are not liable for damage to people or things deriving from improper use of the product. We reserve the right to modify the data contained therein as a result of improvements and technical progress.